



# No-frills Functional Industrial Printer



## **LM4e** Series

### **UNIQUE FEATURES**

- Ideally suited for Logistics and Manufacturing Industries

### **INDUSTRY VERTICALS**

- Logistics
- Supply Chain Management
- Manufacturing

### **APPLICATIONS**

#### **MANUFACTURING, WORK-IN-PROCESS AND MATERIALS TRACKING**

- Picking Labels
- Work-In-Process Labels
- Inventory Control Labels
- Ad-hoc Production Order Labels

#### **SHIPPING AND INVENTORY MANAGEMENT**

- Shipping Labels
- Container/Pallet Labels
- Carton Labels
- Piece Labels
- Packaging Labels
- Routing Labels
- Tracking Labels
- Hub Sortation labels
- Distribution Labels

#### **COMPLIANCE LABELLING**

- Cargo Freight Labels

**Strong & Durable** ▶

**Sturdy Metal Chassis** ▶

**Interface ports for common connectivity options** ▶

**Suitable for Batch Printing** ▶

**Hassle-free loading of fanfold media** ▶

**Easy to load media** ▶



# General Specifications

**LM408/412e****PRINTER MODEL****LM408e****LM412e****PRINTER SPECIFICATIONS**

Printing Resolution	203dpi (8 dots/mm)	305dpi (12 dots/mm)
Max Printing Speed	6ips (153mm/sec)	
Max. Printing Length	3.56mm (14")	
Max. Printing Width	104mm (4.1")	
Print Method	Direct Thermal, Thermal Transfer	

**HARDWARE SPECIFICATIONS**

CPU	32 bit RISC
Memory	Standard memory: 2MB, Expansion memory: 4MB
Selectable Plug-in Interface Cards	IEEE1284, High Speed RS232C, USB, LAN or Wireless LAN
Physical Dimensions	271 (W) × 430 (D) × 321 (H) mm, 10.6" (W) x 16.9" (D) x 12.6" (H)
Power Consumption	AC100-120/200-240V
Regulatory Approvals	CE(TUV), UL, c-UL, FCC(class B), EN55022(class B), EN61000
Operating Environment	Usage: 5~40°C/30~80% Storage: -5~60°C/30~90%
Command	SBPL
Weight	13kg

**CONSUMABLES SPECIFICATIONS**

Media Type	Roll or fan-fold die cut Labels, Plain paper face stock, Synthetics and Continuous stock
Media Width	22mm (0.866") ~ 128mm (5.04") 25mm (0.984") ~ 131mm (5.16") Including Liner
Min Media Length	Continuous: 6mm (0.237"), 9mm (0.354") Including Liner Tear-off: 17mm (0.669"), 20mm (0.787") Including Liner
Maximum Label Roll Diameter	218.4mm (8.6")
Label Roll Core Diameter	76.2mm (3")
Max folding height (for fan-fold fed media)	100mm (3.9")
Label Thickness	0.08mm (0.003") ~ 0.26mm (0.010")
Media Sensor	Reflective Sensor (I-Mark), See-Through Sensor (Gap)
Ribbon Winding Direction	Face in
Ribbon Core Diameter	25.6mm (1")
Ribbon Maximum Length	450m (1.476')
Ribbon Maximum Width	111mm (4.37")

**FONTS/BARCODE SYMBOLOGIES**

Fonts	XU, XS, XM, XB, XL, OCR-4, OCR-B
Character Print Direction	0°, 90°, 180° and 270° rotation in 4 directions
1D Barcode	UPC-A/E, EAN, JAN, CODE39, CODE93, CODE128, UCC/EAN128, Inter-leaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, NW-7, MSI, BookLand, POSTNET, GS1 Databar
2D Barcode	QR code, PDF417, Maxi code, Data matrix

**ACCESSORIES & OPTIONS**

Expansion flash ROM (2MB × 2) (factory shipment option)
---

## Contact

*For more information about SATO around the globe, visit [www.satoworldwide.com](http://www.satoworldwide.com)***AMERICAS**

10350A Nations Ford Road Charlotte, NC  
28273  
Tel: (704) 644-1650  
Fax: (704) 644-1662  
E: [satosales@satoamerica.com](mailto:satosales@satoamerica.com)

**ASIA PACIFIC & OCEANIA**

438B, Alexandra Road,  
#09-01/02, Alexandra Technopark  
Singapore 119968  
Tel: (65) 6271-5300  
Fax: (65) 6273-6011  
E: [sales@satoasiapacific.com](mailto:sales@satoasiapacific.com)

**EUROPE**

Lambroekstraat 5A, 1831 Diegem, Belgium  
Tel: (32) 2 719 03 90  
Fax: (32) 2 719 03 99  
E: [info@be.satoeurope.com](mailto:info@be.satoeurope.com)

For sales & general enquiries: [sales@satoasiapacific.com](mailto:sales@satoasiapacific.com)